

variables/V-color

**Micromotors | Slotless BLDC motor | SVTN
A 02-2057-36-S-O**





Feature

SVTN A 02-2057-36-S-O

Nominal voltage	36 V
No load speed	51286 rpm
No load current	113 mA
Nominal speed	47328 rpm
Nominal torque	15.000 mNm
Nominal current	2.360 A
Stall torque	194.000 mNm
Stall current	29.200 A
Max. efficiency	87.900 %
Terminal resistance*	1.230 ?
Terminal inductance*	0.140 mH
Torque constant	6.680 mNm/A
Speed constant	1430 mNm/V

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

High-Speed Brushless DC Motors

SVTN A 02-2057-36-S-O

Speed/torque gradient	264.00 rpm/mNm
Mechanical time constant	2.500 ms

SVTN A 02-2057-36-S-O

Rotor inertia

0.910 gcm²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.



Advantages

- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy



Benefits

- Light and compact, easy integration
- High reliability
- Good return on investment



expertise in connectivity