variables/V-color

## Micromotors | Coreless DC Motors | SVTN B 01-1725-12-S-OG





	SVTN B 01-1725-12-S-OG
Nominal voltage	12 V
No load speed	10000 rpm
No load current	50 mA
Nominal speed	7400 rpm
Nominal torque	3.280 mNm
Nominal current	0.350 A
Stall torque	12.600 mNm
Stall current	1.170 A
Max. efficiency	67.800 %
Terminal resistance*	10.200 ?
Terminal inductance*	0.310 mH
Torque constant	11.100 mNm/A
Speed constant	833 mNm/V

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## 2 Pole Brushed DC Motors

### SVTN B 01-1725-12-S-OG

Speed/torque gradient793.60 rpm/mNmMechanical time constant5.500 ms

#### SVTN B 01-1725-12-S-OG

#### **Rotor inertia**

0.900 gcm<sup>2</sup>

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.





- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy

- Light and compact, easy integration
- High reliability
- Good return on investment



product engineering services

# expertise in connectivity