Micromotors | Coreless DC Motors | SVTN B 01-3045-12-D-OG





SVTN B 01-3045-12-D-OG

Nominal voltage 12 V

No load speed 7800 rpm No load current 140 mA

Nominal speed 6942 rpm

Nominal torque 18.300 mNm

Nominal current 1.400 A

Stall torque 166.300 mNm

Stall current11.600 AMax. efficiency79.200 %Terminal resistance*1.030 ?

Terminal inductance* 0.110 mH

Torque constant 14.510 mNm/A **Speed constant** 650 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 Pole Brushed DC Motors

SVTN B 01-3045-12-D-OG

Speed/torque gradient 46.90 rpm/mNm

Mechanical time constant 9.140 ms

SVTN B 01-3045-12-D-OG

Rotor inertia

18.620 gcm²

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.



Advantages



Benefits

- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy

- Light and compact, easy integration
- High reliability
- Good return on investment



expertise in connectivity