Micromotors | Coreless DC Motors | SVTN B 01-3571-15-D-OG





SVTN B 01-3571-15-D-OG

Nominal voltage 15 V

No load speed 7100 rpm No load current 160 mA

Nominal speed 6497 rpm

Nominal torque 81.760 mNm

Nominal current 4.230 A

Stall torque 961.900 mNm

Stall current 48.000 A Max. efficiency 88.800 % Terminal resistance* 0.310 ?

Terminal inductance* 0.120 mH

Torque constant 20.110 mNm/A **Speed constant** 473 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 Pole Brushed DC Motors

SVTN B 01-3571-15-D-OG

Speed/torque gradient 7.40 rpm/mNm

Mechanical time constant 5.870 ms

SVTN B 01-3571-15-D-OG

Rotor inertia

76.010 gcm²

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.



Advantages



Benefits

- Winding technology without metal bodies
- Good heat dissipation and high overload capacity
- Long life expectancy

- Light and compact, easy integration
- High reliability
- Good return on investment



expertise in connectivity