Magnetic Tool | COBOT Series | COBOT SMARTMAGGRIP E30





COBOT SMARTMAGGRIP E30

Weight 0.90 kg

Max Breakaway 1 56.30 kg

Working Load 2 14.00 kg

Max shear 18.00 kg

Overall Height 170.00 mm

Magnetic pole footprint 36x31 mm

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Electrical actuation, variable field output, integrated sensors

Finally, the electrical control of magnets integrated into the brand-new E series. It combines Magswitch's patented magnetic technology and SMART features with electrical switching. This provides a new functionality of Variable Field Output (VFO), allowing for de-stacking of thin parts or optimizing performance for your target piece. Once the part is clear of adjacent parts, the tool can be fully switched for maximum performance.

¹ Safety factor 2:1

² Safety factor 4:1





- Electrical actuation of PERMANENT magnets
- Fail safe when actuated at 100%
- Destack, bin pick target parts with different thickness or sizes with one single tool
- Control via CANOpen and power supply through a single M12 connector

- Limited maintenance costs
- Limited peripheral equipment costs
- Very low power consumption
- Reduced cycle time
- Controlled integration costs



expertise in connectivity