

ROBOT TOOL CHANGERS | | EPSILON E50





B Feature

	Master Adaptor	Tool Adaptor
Reference	ER50	ET50
Payload	25 kg	
Moment - Mx, My	88 Nm	
Size	85x85x48 mm	85x85x48 mm
Weight	0.590 kg	0.590 kg
Couple/uncouple port	G1/8	n/a
Repeatability - X, Y	0.020 mm	
Repeatability - Z	0.020 mm	
Maximum Axial Tensile Force (no damage if exceeded)	3.336N @ 0 bar couple port input pressure	

Operating conditions

Operating temperature	5-60°C
Operating pressure	6 bar ±1
User pneumatic pressure	6 bar ±1

EPSILON EXCEPTIONAL LIFTING FORCE FOR A SMALL FOOTPRINT

The line was designed to be a comprehensive family of tool changers that cover the entire range of the current CXC, MXC and Sigma tool changers we already make (ranging from 10kg. to 1,500kg.)

This is a Tool Changer Evolution. Our cam design has stood the test of time and even with extensive research; we couldn't do anything better. In fact, we are so confident in our locking mechanism that we offer a lifetime guarantee on it. We also made sure to incorporate new market requirements and customer feedback to design these tool changers; that's why we extended the availability of couple/uncouple sensing and came up with a direct bolt design to limit the need of adaptor plates.



🖒 Advantages



Maximul robot payload still available

Reduced maintenance cost

Minimized total cost of ownership

Easier installation, less accessories costs



Optional Tool Present Sensing

8x G1/8 User Pneumatic Ports

Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T:+32 (0)65 76 40 40 E:service@pes-sa.com