## **Robot Tool Changers | | Epsilon E50**





	Master Adaptor	<b>Tool Adaptor</b>	
Reference	ER50	ET50	
Payload	25 kg		
Moment - Mx, My	88 Nm		
Moment - Mz	120 Nm		
Size	85x85x48 mm	85x85x48 mm	
Weight	0.590 kg	0.590 kg	
Couple/uncouple port	G1/8	n/a	
Repeatability - X, Y	0.020 mm		
Repeatability - Z	0.020 mm		
<b>Maximum Axial Tensile Force (no</b>	3.336N @ 0 bar couple port		
damage if exceeded)	input pressure		



### **Operating conditions**

Operating temperature 5-60°C Operating pressure 6 bar  $\pm 1$  User pneumatic pressure 6 bar  $\pm 1$ 

# **Epsilon exceptional lifting force for a small footprint**

The line was designed to be a comprehensive family of tool changers that cover the entire range of the current CXC, MXC and Sigma tool changers we already make (ranging from 10kg. to 1,500kg.)

This is a Tool Changer Evolution. Our cam design has stood the test of time and even with extensive research; we couldn't do anything better. In fact, we are so confident in our locking mechanism that we offer a lifetime guarantee on it. We also made sure to incorporate new market requirements and customer feedback to design these tool changers; that's why we extended the availability of couple/uncouple sensing and came up with a direct bolt design to limit the need of adaptor plates.



#### Advantages

• High Strength Aluminum Alloy Body



#### **Benefits**

- Cam Locking Mechanism with:
- Lifetime Guarantee
  - Self-Centering
  - Wear Compensating
  - o Self-Cleaning
  - Positive Cam Retraction
- Optional Couple/Uncouple Sensing
- Optional Tool Present Sensing
- 8x G1/8 User Pneumatic Ports

- Maximul robot payload still available
- Reduced maintenance cost
- Minimized total cost of ownership
- Easier installation, less accessories costs



## expertise in connectivity