

This miniature gripper is lightweight and offers long strokes.

The grippers has a low height and can operate at low speed even with long attachments.

## Feature

	CH93
Course	20 mm
Air consumption	1900 mm³
Function	Double effet
Max cycle per minute	90 cycles
Gripping force*	48.000 N
Weight	0.280 kg
Max. weight of one attachment	0.055 kg
Туре	Parallel 2 jaws

## Operating conditions

Working media	Filtered air	
Operating pressure	3 to 7 bar	
Working temperature	5 to 60°C	
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)	
Repeatability*	Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm	
Lifetime	2 million cycles (with balanced load on each finger)	

## PARALLEL TYPE CUBE GRIPPER, STROKE FROM 10 TO 20MM

\*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

**Notice**: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Our wide range of 2-jaws parallel grippers can be used for chucking extremely small parts to biggest ones. Indeed, NKE 2-jaws grippers are available in various sizes, gripping forces and strokes.





Compact-Lightweight-Fast

Silent mechanism

Quick and simple integration

Large opening angle

Position sensors

No maintenance

Very short cycle time

Excellent power/volume ratio

Low air consumption

