


variables/V-color

Gripper | Parallel 2 jaws | CH93





Feature

CH93

| | |
|--------------------------------------|----------------------|
| Course | 20 mm |
| Air consumption | 1900 mm ³ |
| Function | Double effet |
| Max cycle per minute | 90 cycles |
| Gripping force* | 48.000 N |
| Weight | 0.280 kg |
| Max. weight of one attachment | 0.055 kg |
| Type | Parallel 2 jaws |



Operating conditions

| | |
|----------------------------|---|
| Working media | Filtered air |
| Operating pressure | 3 to 7 bar |
| Working temperature | 5 to 60°C |
| Lubrication | Normally not required (but if necessary, use ISOVG32 compliant lubricant) |
| Repeatability* | Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm |
| Lifetime | 2 million cycles (with balanced load on each finger) |

Parallel type Cube Gripper, stroke from 10 to 20mm

*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Our wide range of 2-jaws parallel grippers can be used for chucking extremely small parts to biggest ones. Indeed, NKE 2-jaws grippers are available in various sizes, gripping forces and strokes.



Advantages

- Compact-Lightweight-Fast
- Silent mechanism
- Quick and simple integration
- Large opening angle
- Position sensors



Benefits

- No maintenance
- Very short cycle time
- Excellent power/volume ratio
- Low air consumption



expertise in connectivity