


variables/V-color

Gripper | Parallel 2 jaws | CH10L





Feature

CH10L

Course	6 mm
Air consumption	500 mm ³
Function	Double effet
Max cycle per minute	60 cycles
Weight	0.140 kg
Max. weight of one attachment	0.040 kg
Type	Parallel 2 jaws



Operating conditions

Working media	Filtered air
Operating pressure	3 to 7 bar
Working temperature	5 to 60°C
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)
Repeatability*	Initial value : ± 0.1 mm, after 2 million cycles : ± 0.2 mm
Lifetime	2 million cycles (with balanced load on each finger)

Parallel type Cube Gripper, stroke from 6 to 60mm

*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar.

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Our wide range of 2-jaws parallel grippers can be used for chucking extremely small parts to biggest ones. Indeed, NKE 2-jaws grippers are available in various sizes, gripping forces and strokes.

The CH10 Series offers 5 gripper models providing two jaws positions (axial and radial). These grippers come with integrated dust protection (rubbing seal) and allow dust cover installation to enhance protection level. Position sensors may also be mounted on the unit body.



Advantages

- Compact-Lightweight-Fast
- Silent mechanism
- Quick and simple integration
- Large opening angle
- Position sensors



Benefits

- No maintenance
- Very short cycle time
- Excellent power/volume ratio
- Low air consumption



expertise in connectivity