



Slotless BLDC motor

High Speed - Long Lifespan - Cost Effective Low Inertia - High Efficiency - Low Noise - High Reliability

 Feature

SVTN A 02-1644-24-S-O	
Nominal voltage	24 V
No load speed	30580 rpm
No load current	95 mA
Nominal speed	28134 rpm
Nominal torque	7.500 mNm
Nominal current	1.100 A
Stall torque	93.800 mNm
Stall current	12.700 A
Max. efficiency	83.400 %
Terminal resistance*	1.900 Ω
Terminal inductance*	0.120 mH
Torque constant	7.440 mNm/A
Speed constant	1284 mNm/V

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

HIGH-SPEED BRUSHLESS DC MOTORS

SVTN A 02-1644-24-S-O

Speed/torque gradient	326.00 rpm/mNm
Mechanical time constant	2.800 ms
Rotor inertia	0.820 gcm ²

Typically employed in the medical field for surgical tools, these motors merge the SVTN A Series characteristics to an optimized project for high-speed functions. Thanks to a precise balancing of the rotor and the use of special bearings, maximum stability, and low noise are guaranteed.

Advantages

Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy

Benefits

Light and compact, easy integration

High reliability

Good return on investment



Zoning de la Rivière, 65
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40
E : service@pes-sa.com