

The CHL601 Series grippers have a slim design and offers strong gripping forces.

## Feature

	CHL601
Course	20-10°
Air consumption	250 mm³
Function	Double effet
Max cycle per minute	90 cycles
Weight	0.054 kg
Туре	Angular 2 jaws

## Operating conditions

Working media	Filtered air
Operating pressure	3 to 7 bar
Working temperature	5 to 60°C
Lubrication	Normally not required (but if necessary, use ISOVG32 compliant lubricant)
Repeatability*	Initial value : $\pm$ 0.1 mm, after 2 million cycles : $\pm$ 0.2 mm
Lifetime	2 million cycles (with balanced load on each finger)

## ANGULAR TYPE SMALL GRIPPER, ANGLE 20~-10°

\*The values of gripping force in the above table indicates pressure at the top edge of the fingers when gripping with pressure of 5 bar

**Notice**: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

Their simple design makes them a robust and reliable solution.



Benefits

Compact-Lightweight-Fast

Silent mechanism

Quick and simple integration

Large opening angle

Position sensors

No maintenance

Very short cycle time

Excellent power/volume ratio

Low air consumption



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T:+32 (0)65 76 40 40 E:service@pes-sa.com