MICROMOTORS | CORELESS DC MOTORS | SVTN B 01-2225-06-S-OG



Coreless DC Motor

High Power Density - High Efficiency - High Reliability Low Inductance - Low Inertia - Good Heat Dissipation Long Operational Lifetime - Cost Effective - No Cogging

Feature

	SVTN B 01-2225-06-S-OG
Nominal voltage	6 V
No load speed	13500 rpm
No load current	100 mA
Nominal speed	11340 rpm
Nominal torque	3.670 mNm
Nominal current	0.980 A
Stall torque	22.900 mNm
Stall current	5.600 A
Max. efficiency	75.100 %
Terminal resistance*	1.070 Ω
Terminal inductance*	0.025 mH
Torque constant	4.170 mNm/A
Speed constant	2250 mNm/V

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 POLE BRUSHED DC MOTORS

	SVTN B 01-2225-06-S-OG
Speed/torque gradient	588.90 rpm/mNm
Mechanical time constant	18.070 ms
Rotor inertia	2.930 gcm²

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.





Winding technology without metal bodies

Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration

High reliability

Good return on investment

