## MICROMOTORS | CORELESS DC MOTORS | SVTN B 01-2230-12-S-OM



Coreless DC Motor

High Power Density - High Efficiency - High Reliability Low Inductance - Low Inertia - Good Heat Dissipation Long Operational Lifetime - Cost Effective - No Cogging



	SVTN B 01-2230-12-S-OM
Nominal voltage	12 V
No load speed	10200 rpm
No load current	24 mA
Nominal speed	9078 rpm
Nominal torque	2.730 mNm
Nominal current	0.270 A
Stall torque	24.900 mNm
Stall current	2.260 A
Max. efficiency	80.400 %
Terminal resistance*	5.310 Ω
Terminal inductance*	0.360 mH
Torque constant	11.120 mNm/A
Speed constant	850 mNm/V

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## 2 POLE BRUSHED DC MOTORS

	SVTN B 01-2230-12-S-OM
Speed/torque gradient	410.40 rpm/mNm
Mechanical time constant	10.630 ms
Rotor inertia	2.470 gcm <sup>2</sup>

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.





Winding technology without metal bodies Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration High reliability Good return on investment



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T : +32 (0)65 76 40 40 E : service@pes-sa.com

expertise in connectivity for innovative solutions

www.pes-sa.com