MICROMOTORS | CORELESS DC MOTORS | SVTN B 01-2863-06-S-WG



Coreless DC Motor

High Power Density - High Efficiency - High Reliability Low Inductance - Low Inertia - Good Heat Dissipation Long Operational Lifetime - Cost Effective - No Cogging



	SVTN B 01-2863-06-S-WG
Nominal voltage	6 V
No load speed	7500 rpm
No load current	320 mA
Nominal speed	6675 rpm
Nominal torque	19.630 mNm
Nominal current	2.920 A
Stall torque	178.500 mNm
Stall current	24.000 A
Max. efficiency	78.200 %
Terminal resistance*	0.250 Ω
Terminal inductance*	0.030 mH
Torque constant	7.540 mNm/A
Speed constant	1250 mNm/V

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

2 POLE BRUSHED DC MOTORS

	SVTN B 01-2863-06-S-WG
Speed/torque gradient	42.00 rpm/mNm
Mechanical time constant	7.020 ms
Rotor inertia	15.940 gcm ²

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.





Winding technology without metal bodies Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration High reliability Good return on investment



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T : +32 (0)65 76 40 40 E : service@pes-sa.com

expertise in connectivity for innovative solutions

www.pes-sa.com