## MICROMOTORS | CORELESS DC MOTORS | SVTN B 01-3045-06-S-WG



Coreless DC Motor

High Power Density - High Efficiency - High Reliability Low Inductance - Low Inertia - Good Heat Dissipation Long Operational Lifetime - Cost Effective - No Cogging



	SVTN B 01-3045-06-S-WG
Nominal voltage	6 V
No load speed	4800 rpm
No load current	95 mA
Nominal speed	4272 rpm
Nominal torque	12.620 mNm
Nominal current	1.160 A
Stall torque	114.700 mNm
Stall current	9.800 A
Max. efficiency	81.300 %
Terminal resistance*	0.610 Ω
Terminal inductance*	0.072 mH
Torque constant	11.820 mNm/A
Speed constant	800 mNm/V

**Notice :** The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

## 2 POLE BRUSHED DC MOTORS

	SVTN B 01-3045-06-S-WG
Speed/torque gradient	41.80 rpm/mNm
Mechanical time constant	6.570 ms
Rotor inertia	14.990 gcm <sup>2</sup>

The specific design construction of a coreless DC motor provides several advantages over the traditional, iron core, technology. A first added value it is given by rotor lower mass and inertia, so very rapid acceleration and deceleration rates are possible. Furthermore, the lack of iron reduces "iron losses" to provide higher efficiencies (up to 90 percent) than traditional DC motors. Last, but not least, the coreless design reduces winding inductance, so sparking between the brushes and commutator is reduced, increasing motor life and reducing electromagnetic interference (EMI). Our Coreless DC Motors are available on a wide range of sizes and we can show high flexibility on custom requirements.





Winding technology without metal bodies Good heat dissipation and high overload capacity

Long life expectancy

Light and compact, easy integration High reliability Good return on investment



Zoning de la Rivièrette, 65 7330 Saint-Ghislain (Belgium) T : +32 (0)65 76 40 40 E : service@pes-sa.com

expertise in connectivity for innovative solutions

www.pes-sa.com