MICROMOTORS | FLAT BRUSHLESS DC MOTORS | SVTM F 03-130-24-D-WO



High Power Density - High Torque - High Efficiency Cost-effective - Compact - Customizable

Feature

	SVTM F 03-130-24-D-WO
Nominal voltage	24 V
No load speed	6100 rpm
No load current	0 mA
Nominal speed	4840 rpm
Nominal torque	130.000 mNm
Nominal current	3.490 A
Stall torque	390.000 mNm
Stall current	11.000 A
Terminal resistance*	0.560 Ω
Terminal inductance*	0.270 mH
Torque constant	37.200 mNm/A

Notice: The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.

BRUSHLESS DC COMPACT MOTOR

	SVTM F 03-130-24-D-WO
Rotor inertia	181.000 gcm²

The natural geometry of the outrunner Brushless Flat Motors, as well as the iron core winding, are the perfect fit for applications requiring high-torque in reduced dimensions. Simplified design, high-end material selection, and automated manufacturing make Flat Motors a high-performance solution at a competitive price. Our vocation in listening to the client's requirements has led us to develop a customization-minded offer, focusing on specific application requirements such as integrated feedbacks, special cables, and custom shape of shafts and flanges.

Advantages



Compact Con

High Torque

High-quality materials and automated manufacturing

Highly customuizable

Compact motor leads to compact design

High Efficiency

Good quality/price ratio

Better and easier integration

