



 Feature

	Master Adaptor	Tool Adaptor
Reference	G-MGW050-2O	G-MGW050-2U
Payload	40 kg	
Moment - Mz	48 Nm	
Repeatability - X, Y	0.020 mm	
Maximum Axial Tensile Force (no damage if exceeded)	AL, Anod.	

 Operating conditions

Operating temperature	5-60°C
Operating pressure	6 bar ±1

# THE UNIVERSAL MGW CONNECTOR - SAFER AND MORE PRECISE TOOL CHANGER FOR YOUR APPLICATIONS.

Our manual tool changers range aims at solving quick equipment change issues for many applications. These tool changers can be seen as quick, repeatable, and reliable mechanical connectors that can serve many purposes: robot tooling change, special machinery utility change or even making a tool stand movable. Installing such a kind of quick connection device makes your equipment versatile, and upgradable, and eases maintenance operation while reducing downtimes.



## Advantages

Withstands high loads with low dead weight

Can be released and closed with one handle

During locking, the lower assembly is pulled around the locking stroke

Interface according to DIN EN ISO 9409-1



## Benefits

Does not require a deep review of the mechanical structure to be integrated.

Cost savings through reduced maintenance downtime.

Improved equipment versatility and upgradability and then extended productivity.

Mitigate the need of specifically designed mounting interfaces



**pes**

product  
engineering  
services

Zoning de la Rivière, 65  
7330 Saint-Ghislain (Belgium)

T : +32 (0)65 76 40 40  
E : service@pes-sa.com