variables/V-color

Slip Ring | 18 circuits | SVTS A 03-S-X-00/18



Slip ring specially suited to transmit critical signals, such as hi frequency and data rate, low current and voltages (strain gauges, thermocouples, measuring equipment, etc.) and offering a optionnal fieldbus or Ethernet channel (EtherCAT, Profinet, Profibus, etc.).



SVTS A 03-S-X-00/18

Circuits18 x 2AOutside Diameter22.00 mm mmOverall Length (L)33.40 mm mmProtection ratingIP 51Data Transfert<=100Mbit/s</th>MountingFlange / Capsule



Mechanical features

0-250 rpm
-20° C to $+80^{\circ}$ C (-40° C as option)
gold-gold (alloy)
Miniature high-precision stainless steel ball bearings
-
ABS



Electrical features

Voltage Cables Cables length Dielectric voltage strength 240 VDC/VAC Silver plated / PTFE insulated / colour coded 250 mm standard (other length on request) 500VAC @ 60Hz @ 60 sec

Insulation resistance	>500MOhm/500VDC
Dynamic contact resistance	10mOhm @ 6VDC and 500mA (@ 5rpm)
Expected lifetime	10 ⁷ revolutions (depending on speed, environmetal conditions and size)

Notice : The provided technical data are the higher limits recommended in static condition. To obtain the correct dimensioning of the product, it is necessary to hold account of all the applicable dynamic forces, including the inertia of the manipulator, the configuration of the tools and the external forces applied.





- Option : 100 Base-TX or 1000 Base-T channel with RJ45 plug
- High data rate
- Gold alloy rings and brushes
- Low friction torque
- High lifetime and reliability
- Compliant to CE and ROHS

Customisations

- Cables
- Materials
- Mechanical design

- Optimal signal transmission (gold-gold technology)
- Cost-effective

• Flange

product engineering services

expertise in connectivity