



IND-MAX inductive angle encoders provide robust, high-precision measurement in extreme environment applications across land, sea, and air.

 **System Data**

IND-MAX-375	
Type	Axial, frameless, true absolute, inductive measuring principle
Standard Resolution	23 bits
ENOB in entire mounting tolerance range	22 bits
High Accuracy	Enhanced accuracy can be achieved depending on the mounting setup
Standard Accuracy	$\pm 007^\circ, \pm 0.002^\circ, \pm 035 \mu\text{rad}$
Thickness	14.20
Hysteresis	none
Repeatability	1 resolution count
Position update rate and signal latency	Real-time
Power-up Time	max. 0.8 sec

 **Electrical Data**

Supply voltage	min.4.35Vdc.max.36Vdc
----------------	-----------------------

Reverse polarity protection	yes
Current Consumption	max. 150 mA @ 5 Vdc max. 50 mA @ 24 Vdc

## Mechanical Data

Stator Base Material	Anodized aluminum CTE ~ 24 ppm/°C
Stator Weight	525.00 g
Rotor Base Material	Anodized aluminum CTE ~ 24 ppm/°C
Rotor Weight	375.00 g
Vibration	EN 60068-2-6, 20 g, 55 .. 2000 Hz
Shock	EN 60068-2-27, 200 g, 6 ms

## Mounting Tolerances

Nominal Axial (air-gap)	0.50 mm
Axial Tolerance	0.30 mm (0.20 mm to 0.80 mm)
Radial Tolerances	0.20 mm

## Environmental Data

Temperature Range - Standard Operating	-20°C .. +85°C
Temperature Range - Standard Storage	-20°C .. +85°C
Temperature Range - Extended Operating	-40°C .. +105°C
Temperature Range - Extended Storage	-55°C .. +125°C
Ingress Protection	IP67
EMC Immunity	complies with EN IEC 61000-6-2
EMC Emission	complies with EN IEC 61000-6-4

## Advantages

Plug-n-play

No field calibration required

Wide mounting tolerances

High accuracy

## Benefits

Low installation cost

Low integration effort

Easy installation